

ACTINO

DENTAL ETCHING LIQUID

PREVESTDenPro®
THE FUTURE OF DENTISTRY

Product Description : Actino is a Blue tinted viscous liquid of 37% Phosphoric acid, silica free composition recommended for use on enamel and dentine. Its non drying thixotropic liquid composition prevents thickening and dry out with time and thus maintain its flow characteristics.

Composition : Phosphoric Acid, Colouring Agent, Purified Water and Thickening agent.

Intended Purpose / Intended Use : It is intended to be used for enamel and dentin etching.

Indications for Use : Used for conditioning both dental enamel and dentine surfaces prior to the placement of an adhesive restoration.

Instructions for Use :

1. Isolate the tooth using a rubber dam. Prepare the tooth or cavity, clean and dry the area prior to etchant application.
2. Remove the protective cap from the bottle and dispense the required amount of material on a dispensing pad.
3. Use application brush to apply a thin layer of Actino to the areas to be etched. Allow the liquid to stay for 10-15 seconds and then rinse thoroughly with water spray. Dry etched tooth surface with clean, dry air.
4. The dispensed material shall not be placed back in container and the dose once applied and used shall not be reused.

Warning : Avoid prolonged or repeated contact with skin (allergic contact dermatitis), and eyes. Avoid prolonged inhalation. Do not take internally. Contact with the skin may cause irritation, burns of hypersensitivity. If contact with skin occurs immediately wipe off thoroughly with cotton and alcohol and then wash well with soap and water. If skin rash and sensitization or other allergic reaction occurs discontinue use and seek medical attention. If the product comes into contact with the eyes, rinse thoroughly with fresh water and consult a physician.

Precautions : The product contains phosphoric acid. It can burn and cause irritation to the tissues and therefore confine the use to areas to be etched. Avoid contact with eyes and prolonged contact with skin.

Contraindications : The products contains 37% Phosphoric acid, so the product should not be used with patients who have a history of severe allergic reaction to any of the components. Do not use on exposed pulp.

Storage Conditions :

Store at temperature between 10°C(50°F) to 24°C(75°F). Close the cap carefully after use. Keep away from moisture. Shelf life not affected after opening if stored in a cool dry place.

Shelf Life : 3 years from the date of manufacturing.

Presentation :

Ref: 10009

10ml Plastic dropper bottle.

Disposal conditions : To be disposed off based on the prevailing rules of the country in which it is used.

Prevest DenPro Limited
Unit II, Export Promotion Industrial Park,
(EPIP), Bari Brahmna, Jammu-181133,
India. www.prevestdenpro.com
Customer Care No. : + 91 8899074151
Email : customercare@prevestdenpro.com
Made in India

E C R E P
Obelis s.a
Boulevard General Wiclis 53
1030 Brussels, Belgium
Tel: +32 2 732 99 54, Fax: +32 2 732 60 03
E-mail : mail@obelis.net

CE
0123

Revision :	08
Date :	11-09-2024

MD Symbol for "MEDICAL DEVICE" **UDI** Symbol for "UNIQUE DEVICE IDENTIFIER"

LOT Symbol for "BATCH CODE" **USE-BY DATE** Symbol for "USE-BY DATE" **STERILE** Symbol for "NON STERILE" **KEEP DRY** Symbol for "KEEP DRY"

CAUTION Symbol for "CAUTION" **CONSULT INSTRUCTION FOR USE** Symbol for "CONSULT INSTRUCTION FOR USE" **REF** Symbol for "CATALOGUE NUMBER"

EC REP Symbol for "AUTHORIZED REPRESENTATIVE IN THE EUROPEAN COMMUNITY/EUROPEAN UNION"

DO NOT USE IF PACKAGE IS DAMAGE Symbol for "DO NOT USE IF PACKAGE IS DAMAGE" **KEEP OUT OF THE REACH OF CHILDREN** Symbol for "KEEP OUT OF THE REACH OF CHILDREN" **MANUFACTURER** Symbol for "MANUFACTURER"

TEMPERATURE LIMIT Symbol for "TEMPERATURE LIMIT" **KEEP AWAY FROM SUNLIGHT** Symbol for "KEEP AWAY FROM SUNLIGHT" **CORROSIVE** Symbol for "CORROSIVE"

The material has been developed solely for professional dental use. Application should be carried out strictly according to the instruction for use. Liability cannot be accepted for damages resulting from failure to observe the instructions of the stipulated area of applications. The user is responsible for testing the material for its suitability and use for any purpose not explicitly stated in this instruction sheet. Description and data constitute no warranty of attributes and are not binding. For feedback, complaints and reporting of unexpected events contact customer care.