IFU Size: 161 H x 104 W

ZINCONOL



POLYMER REINFORCED ZOE CEMENT

Product Description:

Zinconol is a polymer reinforced zinc oxide eugenol cement for temporary restoration. The excellent physical properties resulting from the unique polymer reinforcing agents include high compressive and tensile strength, excellent abrasion resistance and low solubility. Its strength is comparable to Zinc Phosphate Cement.

Composition:

Powder contains Zinc Oxide, Fillers and Accelerators and Liquid contains Eugenol and Fillers Intended Purpose/Intended Use: It is intended to be used as a temporary filling material

Indications for Use:

Intermediate restorative material (IRM) for class I & II restorations. Temporary restoration in emergency treatments and to seal the coronal portion of the teeth under endodontic treatment. As a base under amalgam and non resin restorations.

Instructions for Use:

Shake the bottle of powder well before use to ensure that the density is homogeneous. Powder and liquid should be mixed in proper ratio. Powder liquid ratio is 1:2 (2 scoop powder and 2-3 drops liquid.) Mixing should be completed in 45-60 seconds to a putty consistency. Insert into the cavity and allow 4-6 minutes for proper hardening. The dispensed material shall not be placed back in container and the dose once applied and used shall not be reused.

Warnings:

Avoid prolonged or repeated contact with skin (allergic contact dermatitis), and eyes. Avoid prolonged inhalation. Do not take internally. Contact with the skin may cause irritation, burns of hypersensitivity. If contact with skin occurs, immediately wipe off thoroughly with cotton and alcohol and then wash well with soap and water. If skin rash and sensitization or other allergic reaction occurs, discontinue use and seek medical attention. If the product comes into contact with the eyes, rinse thoroughly with fresh water and consult a physician. It should not be used with patients who have a history of severe allergic reaction to any of the components.

Precautions: Zinconol is a Eugenol based compositions and therefore it should not be used as a liner under resin based filling materials. Avoid contact with eyes. Do not invert the bottle upside down while opening to avoid excess dispensing of the powder and avoid excessive force while dispensing the liquid from the dropper.

Contraindications: It is contraindicated for use with patient who have a history of severe allergic reaction to any of the components.

Storage Conditions:

Store at temperature between 10°C (50°F) and 24°C (75°F).. Close the cap carefully after use. Keep away from moisture. Shelf life not affected after opening if stored in a cool dry place.

3 years from the date of manufacturing.

Presentation:

Ref: 30015

15g Powder, 10ml Liquid, Spoon, Mixing Pad and Dispensing Dropper.

75g Powder, 40ml Liquid, Spoon, Mixing Pad and Dispensing Dropper.

Disposal conditions: To be disposed off based on the prevailing rules of the country in which it is used.

Prevest DenPro Limited

Unit II, EPIP, Bari Brahmana, Jammu-181133, India. www.prevestdenpro.com

Customer Care No.: +91 8899074151

Email: customercare@prevestdenpro.com Made in India

reporting of unexpected events contact customer care.

E C REP Obelis s.a evard General Wahis 53 1030 Brussels, Belgium Tel: +(32) 2 732 59 54, Fax. +(32) 2 732 60 03 E-mail : mail@obelis.net

Issue/Revision: 01/00 08-02-2023 Date:

UDI Symbol for "UNIQUE DEVICE IDENTIFIER"

Symbol for "BATCH CODE" Symbol for "USE-BY DATE" Symbol for "NON STERILE" Symbol for "KEEP DRY" Symbol for "CAUTION" [] Symbol for "CONSULT INSTRUCTION FOR USE" REF Symbol for "CATALOGUE NUMBER" ECTREP Symbol for "AUTHORIZED REPRESENTATIVE IN THE EUROPEAN COMMUNITY/EUROPEAN UNION

Symbol for "DO NOT USE IF PACKAGE IS DAMAGE" Y Symbol for "KEEP OUT OF THE REACH OF CHILDREN" W Symbol for "MANUFACTURER" "Symbol for "TEMPERATURE LIMIT" 🌋 Symbol for "KEEP AWAY FROM SUNLIGHT" 🔟 Symbol for "MEDICAL DEVICE"

The material has been developed solely for professional dental use. Application should be carried out strictly according to the instruction for use. Liability cannot be accepted for damages resulting from failure to observe the instructions of the stipulated area of applications. The user is responsible for testing the material for its suitability and use for any purpose not explicitly stated in this instruction sheet. Description and data constitute no warranty of attributes and are not binding. For feedback, complaints and